

PRIMACOAT GREEN

Specification sheet



Primacoat Green is the first woodfree coated thin paper containing 75% recycled fibres. Launched in October 2010 as part of the development of new eco-friendly paper solutions, Primacoat Green is the first product to come out of Bolloré Thin Papers “eco-design cell”. Its whiteness, high opacity and excellent print quality make it the ideal paper for books, catalogues & mail shots.

FSC or PEFC on request

Specifications					
Characteristics	Unit	Standard			
Code			PCG50WSB	PCG55WSB	PCG60WSB
Grammage	g/m ²	ISO 536	50 g/m ²	55 g/m ²	60 g/m ²
Grammage (USA)	lbs		33.8	37.2	40.5
Bulk	cm ³ /g		0.96	0.96	0.97
Thickness	µm	ISO 534	48	53	58
ISO Whiteness	%	ISO 2470	87	87	87
CIE Whiteness		ISO 11475	131	131	131
Opacity	%	ISO 2471	87	88.5	90
Brilliant	%	ISO 2813	29	30	31
FCR	%			75	
Absolute humidity	%	NF Q03-003		5.7	
Optical brightner	-	-			

Paper tolerances	
Grammage: + / - 1 g/m ²	CIE whiteness: + / - 6 points
Thickness: + / - 3 µm	Minimum Opacity: nominal value 1 point
Minimum brilliance: nominal value - 4 points	Absolute humidity: + / - 0.5%
ISO whiteness minimum: nominal value 1 point	

Minimum making: Quantity required by the mill will be dependent on both the production schedules and the possibilities at the time of the order for a combination of widths to cover the machine deckle. Please contact your sales representative for more details.

Measurement made on Jumbo rolls according to standards and norms in place at that time.

Validated: 02/05/2015

Qualified by Hervé Brunet-Jailly-Technical Support Manager