



Made with 50% recycled fibre, FSC certified and available from 32 g/m<sup>2</sup> to 60 g/m<sup>2</sup> in either a mat or silk finish, Primagreen is the ideal solution in terms of both print & ecological performance: 2,200 tons of CO<sub>2</sub> can be saved each year when compared to the use of a standard thin paper of the same basis weight. Primagreen is perfectly suited to printing mail-order, catalogues, directories, dictionaries, information/travel guides and mail shots. High whiteness & opacity in conjunction with a bulk close to 1.10 cm<sup>3</sup>/g, allows for excellent results when colour printing. Primagreen is available in both reels and sheets.

Specifications								
Characteristics	Unit	Standard						
Code			PRG32WST	PRG36WST	PRG39WST	PRG45WST	PRG50WST	PRG60WST
Grammage	g/m <sup>2</sup>	ISO 536	32 g/m <sup>2</sup>	36 g/m <sup>2</sup>	39 g/m <sup>2</sup>	45 g/m <sup>2</sup>	50 g/m <sup>2</sup>	60 g/m <sup>2</sup>
Grammage (USA)	lbs		21.6	24.3	26.3	30.4	33.8	40.5
Thickness	µm	ISO 534	35	40	43	50	55	66
Bulk	cm <sup>3</sup> /g		1.10	1.10	1.10	1.10	1.10	1.10
PPI ( <i>indicative</i> )			1480	1290	1210	1025	930	770
ISO Whiteness	%	ISO 2470	80	80	80	80	80	80
CIE Whiteness			110	110	110	110	110	110
Opacity	%	ISO 2471	82.5	85	87	88	89	91
FCR	-	ISO 6588	YES					
Absolute humidity	%	NF Q03-003	5.7					
Optical brightner	-	-	NO					

Paper tolerances	
Grammage: nominal value + / - 1 g/m <sup>2</sup>	ISO whiteness minimum: nominal value 1 point
Thickness: + / - 2 µm	CIE whiteness: nominal value + / - 6 points
PPI ( <i>indicative</i> )	ISO opacity minimum: nominal value 1 point
	Absolute humidity: + / - 0.5%

Finished good tolerance
Joins: maximum of 2 joins per reel with at least 60% of the reels being "join free"
Width: customer width - 0 mm, + 2 mm
Outer diameters of 100, 114 or 120 cm : - 3 cm, + 2 cm

*Minimum making: Quantity required by the mill will be dependent on both the production schedules and the possibilities at the time of the order for a combination of widths to cover the machine deckle.  
Please contact your sales representative for more details.*

*Measurements made on Jumbo rolls according to the Standards and Norms in place at that time.*

*Validated: 02/05/2015*

*Qualified by Hervé Brunet-Jailly – Technical Support Manager*