

# PRIMAPAGE NEW white

## Specification sheet



Primapage is a thin opaque uncoated paper dedicated to monochrome printing in either heat set or cold set. The combination of its natural brightness, excellent opacity, the low level of strike through plus a silky touch provides a finished publication which is "easy on the eyes". Primapage is available in both reels and sheets.

**FSC® or PEFC certified on request**

### Specifications

Characteristics	Unit	Standard							
Code			PPG29NEW	PPG33NEW	PPG36NEW	PPG40NEW	PPG45NEW	PPG50NEW	PPG60NEW
Grammage	g/m <sup>2</sup>	ISO 536	29 g/m <sup>2</sup>	33 g/m <sup>2</sup>	36 g/m <sup>2</sup>	40 g/m <sup>2</sup>	45 g/m <sup>2</sup>	50 g/m <sup>2</sup>	60 g/m <sup>2</sup>
Basis weight (USA)	lbs	25*45/500	19,6	22,3	24,3	27,0	30,4	33,8	40,5
Thickness	µm	ISO 534	33,9	38,6	42	47	52,7	58,5	70,2
Bulk	cm <sup>3</sup> /g	-	1,17	1,17	1,17	1,17	1,17	1,17	1,17
PPI (indicative)	pages/inch	T 411	1 554	1 320	1 226	1 090	966	880	720
Whiteness	%	ISO 2470	86	87,5	87,5	87,5	87,5	87,5	87,5
Opacity	%	ISO 2471	80	79,5	80	82	84	86	88
Absolute humidity	%	NF Q03-003	5,7						
Permanent paper	-	ISO 9706	OUI						
Optical brightner	-	-	NON						

### Paper tolerances

Grammage: nominal value + / - 1 g/m <sup>2</sup>	ISO whiteness minimum: nominal value 1 point
Thickness: + / - 2 µm	ISO opacity minimum: nominal value 1 point
PPI (indicative)	Absolute humidity: + / - 0.5%

### Finished goods tolerances

Joins: maximum of 2 joins per reel with at least 60% of the reels being "join free"
Width: customer width - 0 mm, + 2 mm
Outer diameters of 100 cm, 114 cm or 120 cm: - 3 cm, + 2 cm

*Minimum making: Quantity required by the mill will be dependent on both the production schedules and the possibilities at the time of the order for a combination of widths to cover the machine deckle.*

*Please contact your sales representative for more details.*

*Measurements made on Jumbo rolls according to the Standards and Norms in place at that time.*

*Validated: February 2017*

*Qualified by Hervé Brunet-Jailly - Product Manager*